



Hibrid İklimlendirme Mühendislik Enerji Çözümleri ve Dış Ticaret Ltd.



ICE CUBE





DESIGNED FOR  
LARGE AREAS



## Full control of venues

Icecube cassette type air conditioners gives full control. It reaches every point you want to acclimatize with 360° blowing feature. The climate is always under your control with the new generation remote,

# Extra features



**A++** (Cooling)

**A+++** (Heating)

Inverter Technology is a technology that obtains more efficiency and provides more comfort by changing the operating frequency of the motor.




## Sleep Mode

Comfort sleep mode is activated with the off button selected before sleep, thus preventing overheating and cooling during the night.



%60 energy saving  
R32 refrigerant



## Bio Filter

BioFilter blocks harmful bacteria and keeps the air clean and fresh.




**29dB**

Ultra Quiet  
Operation




**-15°C**

Runs even at -15  
degrees



360°C  
blowing places with  
full control



## Turbo Mode



24000BTU-42000BTU - 55000BTU



ICE CUBE



**ICE CUBE**

MODEL		ICECUBE 24	ICECUBE 42	ICECUBE 55
Cooling Capacity	kW	7.0	12.1	14,0
	Btu	24000 (11263~27000)	41000 (10000~42000)	48000 (12000~54000)
Heating Capacity	kW	6.0	9.5	11,0
	Btu	26000 (9577~30500)	46000 (11500~48000)	55000 (14000~59000)
SEER/SCOP	W/W	6.2	6,1	6,1
Working Current (Cooling)	A	10.2 (4.2~12)	18.8 (3.1~19.1)	8.1 (1.8~10.2)
Electric Power (Cooling)	W	2320 (780~2748)	4200 (680~4350)	4650 (800~5900)
Working Current (Heating)	A	8.5 (3.6~12.1)	16.3 (3.4~19)	8.0 (1.9~9.5)
Electric Power (Heating)	W	1900 (610~2700)	3700 (750~4250)	4580 (900~5500)
<b>OUTDOOR</b>		<b>ICECUBE 24 OD</b>	<b>ICECUBE 42 OD</b>	<b>ICECUBE 55 OD</b>
Operating Temperature Range (Cooling)	°C	-15 / 50	-15 / 50	-15 / 50
Operating Temperature Range (Heating)	°C	-15 / 24	-15 / 24	-15 / 24
Electricity Supply	-	220-240V,1Ph, 50Hz	220-240V,1Ph, 50Hz	380-415V,3Ph, 50Hz
Energy Class Cooling / Heating	-	A++ / A+	A++ / A+	A++ / A+
Energy Class Heating	-	A+++ (Aegean and Mediterranean Region)	A+++ (Aegean and Mediterranean Region)	A+++ (Aegean and Mediterranean Region)
Refrigerant	kg	1,5 R32	2,8 R32	2,9 R32
Liquid/Gas Copper Pipe	inch	(3/8" / 5/8")	(3/8" / 5/8")	(3/8" / 5/8")
Maximum Pipe Length	m	50	75	75
Maximum Height Difference	m	25	30	30
Sound Power Level	dB(A)	60	63	63.5
Sound Pressure Level	dB(A)	67	71	73
Air Flow	m³/h	3500	4000	7500
Weight	kg	43.9/46.9	71.0/75.0	103.7/118.3
Dimensions (WxDxH) (Device)	mm	890x342x673	946x410x810	952x415x1333
Dimensions (WxDxH) Packaging	mm	995x398x740	1090x500x885	1095x495x1480
<b>INDOOR</b>		<b>ICECUBE 24 ID</b>	<b>ICECUBE 42 ID</b>	<b>ICECUBE 55 ID</b>
Sound Power Level	dB(A)	57	65	65
Sound Pressure Level (high/medium/low)	dB(A)	50/47.5/42/29	52.5/50/47.5/40	52.5/50.5/48/40
Air Flow (high/medium/low)	m³/h	1247/1118/992	1900/1750/1600	1900/1750/1600
Weight (Device)	kg	21.6/25.4	29.3/33.5	29.3/33.5
Dimensions (WxDxH) (Device)	mm	830x830x205	830x830x287	830x830x287
Dimensions (WxDxH) Packaging	mm	910x910x250	910x910x330	910x910x330
<b>INDOOR UNIT PANEL</b>		<b>ICECUBE 24 ID Panel</b>	<b>ICECUBE 42 ID Panel</b>	<b>ICECUBE 55 ID Panel</b>
Weight (Device)	kg	6/9	6/9	6/9
Dimensions (WxDxH) (Panel device)	mm	950x950x55	950x950x55	950x950x55
Dimensions (WxDxH) (Panel) Packaged	mm	1040x1030x90	1040x1030x90	1040x1030x90

The manufacturer has the right to make changes in the product specifications without notice. Our company is not responsible for typographic errors in the catalog. Energy values



**Head Office Istanbul**

Saray Mah. Dorakent Sok. Dorapark Sitesi  
A Blok No:1A Kat:13 Daire :94  
Ümraniye / İSTANBUL

T: +0216 692 01 00  
[www.hibridmuhendislik.com](http://www.hibridmuhendislik.com)

**Branch Office Istanbul**

Meydan İstanbul AVM, Balkan Cd. No:62  
34770 Ümraniye/ İSTANBUL

[info@hibridmuhendislik.com](mailto:info@hibridmuhendislik.com)  
[yuksel@hibridmuhendislik.com](mailto:yuksel@hibridmuhendislik.com)