




Hibrid İklimlendirme Mühendislik Enerji Çözümleri ve Dış Ticaret Ltd.

18000 BTU/h
Cooling (max): 23.000 BTU/h
Heating (max): 23.000 BTU/h



9000 BTU/h
Cooling (max): 11.600 BTU/h
Heating (max): 13.500 BTU/h



24000 BTU/h
Cooling (max): 27.000 BTU/h
Heating (max): 27.000 BTU/h



12000 BTU/h
Cooling (max): 16.200 BTU/h
Heating (max): 14.400 BTU/h



Attractive Design

Beside of the visuality present design provides you to easily get the comfort you need.

Rota Climate Seal makes your life easier with its power and aesthetics.



Climate Under Your Control

Your air conditioning in your control thanks to with high technology of Rota Climate's Superior Features



Extra features



A+++

A+++ Inverter Technology is a technology that obtains more efficiency and provides more comfort by changing the operating frequency of the motor.



Sleep Mode

Comfort sleep mode is activated with the off button selected before sleep, thus preventing overheating and cooling during the night.



%60 energy saving
R32 refrigerant



You can air-condition your home remotely with WiFi technology. WiFi Feature is optional




25dB

Ultra Quiet Operation




-15°C

Runs even at -15 degrees



Wide blade angle spreads comfort throughout the room



Turbo Mode





MODEL		S 09	S 12	S 18	S 24
Cooling Capacity	kW	2,8	3,6	5,2	7,0
Cooling Capacity	Btu/h	9000	12.000	18.000	24.000
Min. - Max. Cooling Capacity	Btu/h	(3100-11600)	(3800-14200)	(6200-21000)	(7100-27000)
P design C	kW	2,8	3,6	5,2	7,0
SEER	W/W	6,3	6,1	7,4	6,1
Energy Class		A++	A++	A++	A++
Working Current (Cooling)	A	3,18	5,27	6,7	11,5
Working Power (Cooling)	kW	732	1213	1550	2600
Heating Capacity	kW	2,6	2,5	4,4	5,6
Heating Capacity	Btu/h	10.000	13.000	19.000	25.000
Min. - Max. Heating Kapasitesi	Btu/h	(2800-11500)	(3700-14400)	(4400-23000)	(5500-27000)
P design H	kW	2,6	2,5	4,4	5,6
SCOP	W/W	5,1	5,1	5,1	5,1
Energy Class		A+++	A+++	A+++	A+++
Working Current (Heating)	A	3,18	4,73	6,8	11
Working Power (Heating)	kW	733	1088	1570	2400
INDOOR					
Sound Power	dB(A)	54	55	56	59
Ses BSound Pressure dB (A)	dB(A)	38,5/32/25	40,5/34,5/25	42,5/36/26	45/40,5/36
Air Flow		466/360/325	540/430/314	840/680/540	980/817/662
Product Weight	kg	7,6/9,7	7,6/9,8	10/13	12,3-15,8
Dimension (W*D*H)	mm	870x270x365 / 805x194x285	870x270x365 / 805x194x285	1035x295x385 / 957 x213x302	1120x405x315 / 1040x220x327
OUT DOOR					
Outdoor Operating Temperature/ Cooling °	°C	-15 / 50	-15 / 50	-15 / 50	-15 / 50
Outdoor Operating Temperature/ Heating °	°C	-15 / 30	-15 / 30	-15 / 30	-15 / 30
Compressor Type		Rotary	Rotary	Rotary	Rotary
Sound Power level	dB(A)	62	63	63	59
Sound Pressure Level dB(A)	dB(A)	55,5	56	56	67
Air Flow		1750	1800	2100	3500
Product Weight KG	kg	23,2 / 25	23,2 / 25	32,7/35,4	42,9/45,9
Dimension (W*D*H)	mm	835x300x540 / 720x270x495	835x300x540 / 720x270x495	915x370x615 / 805x330x554	995x398x740 / 890x342x673
Cooler liquid		R32	R32	R32	R32
Refrigerant kg	kg	0,55	0,55	1,08	1,42
Liquid/Gas Copper	inch	1/4-3/8	1/4-3/8	1/4-1/2	3/8-5/8
Maximum Pipe	m	25	25	30	50
Maximum Height Difference	m	10	10	20	25

The manufacturer has the right to make changes in the product specifications without notice. Our company is not responsible for typographic errors in the catalog. Energy values may show regional variations.

Hibrid İklimlendirme Mühendislik Enerji Çözümleri ve Dış Ticaret Ltd.

Head Office İstanbul

Saray Mah. Dorakent Sok. Dorapark Sitesi
A Blok No:1A Kat:13 Daire :94
Ümraniye / İSTANBUL

T: +0216 692 01 00
www.hibridmuhendislik.com

Branch Office İstanbul

Meydan İstanbul AVM, Balkan Cd. No:62
34770 Ümraniye/ İSTANBUL

info@hibridmuhendislik.com
yuksel@hibridmuhendislik.com

